

- Compact & Lightweight chassis
- IEPE/Charge amplifier, channel selectable
- Individual channel gain selection x1, x10, x100
- Power on indication
- Signal level indicator per channel
- ±10VAC output
- DC powered, Mains adaptor supplied
- Huge flexibility in a low cost per channel unit.



The 3X-CI is a 3 channel IEPE and charge signal conditioning unit, housed in a compact and rugged chassis. Featuring DC power input it can be used via the supplied mains DC adaptor or via a field based DC supply such as battery.

Each channel can be independently switched to be IEPE or Charge signal conditioning. In addition each channel has independent gain control x1, x10, x100. Signal input and output connections are via front panel BNC jack connectors, making connection quick and simple. An earth/floating switch is also included on the rear panel

A signal level indicator is also provided for each channel via a multi coloured LED when in IEPE mode:

- Green – OK
- Red – Short circuit
- Off – Open circuit

Gain setting	Input/Charge	Input/IEPE	Output
X1	1pC	1mV	1mV
X10	1pC	1mV	10mV
X100	1pC	1mV	100mV

Specification	
Channels	3
Power Input	9 – 30 Volts DC, 5 Watt. (nominal 18VDC)
Power connection	2.1mm DC Socket
Signal Connections	BNC Jacks - Input and Outputs on front panel
Indicators - Power	External LED indicator shows correct power to unit
Indicators - Signal	Multi coloured LED per channel, Green – OK/ Red – Short Circuit/ OFF – Open Circuit
Floating or Ground	Selectable via rear panel switch
IEPE power (only in IEPE mode)	24VDC, 4mA
Signal level output	+/- 10 VAC pk-pk
Dimensions	Height - 123mm, Width 45mm, Depth 196mm
Weight	570grams
Operating Temp.	0 to 45 °C, non-condensing.
Broadband Electrical Noise	(1 to 10,000Hz) (Gain x1) 48.1 μVrms
	(1 to 10,000Hz) (Gain x10) 79.7 μVrms
	(1 to 10,000Hz) (Gain x100) 498 μVrms
Bandwidth	Gain x1 500kHz
Bandwidth	Gain x10 500kHz
Bandwidth	Gain x100 100kHz

Due to continued product development Kemo Limited reserve the right to change specification without notice.